

Customize available by user request !

Model	Shuttle inner diameter (mm)	Finished coil inner diameter Min. (mm)	enamelled copper wire diameter(mm)															
			0.06	0.07	0.08	0.09	0.10	0.12	0.13	0.14	0.15	0.16	0.18	0.20	0.22	0.25	0.28	
S4-2.6	87.8	6.6	wire length storage capacity (mm)	71960	51520	38640	29680	23520	15960									
S4-2.6-2	98	6.6		81220	58280	43710	33790	26660	17980	14880								
S4-2.7	103	6.7		118140	84810	63360	49170	38610	26400	21780	18480							
S4-3.0	92	6.9		113390	81490	60900	47270	37410	25230	20880	17690	15660	13050					
S4-3.0-5	98	7			98890	74090	57350	45260	30690	25730	21390	18600	16120	12400				
S4-3.6	98	8				142910	110670	87730	59520	49600	41850	39370	31000	23870	18910			
S4-4.3	99	8.8					190598	151034	102678	85408	72220	61544	54008	41448	32970	26376		
S4-5.0	99	9.7						250572	170188	141928	119634	103620	89490	69080	54636	43960	33284	
S4-5.2	99	9.9							193424	161396	136276	119320	102050	78814	62172	50240	37994	29516
Model	Shuttle inner diameter (mm)	Finished coil inner diameter Min. (mm)	enamelled copper wire diameter(mm)															
			0.08	0.09	0.10	0.12	0.13	0.14	0.15	0.16	0.18	0.20	0.22	0.25	0.28	0.32	0.40	
S6-3.6	135	8.4	wire length storage capacity (mm)	192100	148325	117725	79900	66300	55675	50150	41650	32300						
S6-4.8	137	9.4			391730	310460	210700	175440	147920	128140	110510	85140	67510					
S6-5.2	145	9.9				391460	266340	221720	186760	161920	139840	107640	85100	68540				
S6-5.3	137	10.1					298850	248970	209840	175870	157380	121260	95890	77400	58480			
S6-5.9	137	10.7						283800	239510	206400	179310	138460	109650	88150	66650	52030		
S6-6.4-3	139.3	11.7							314160	286880	235400	181720	143880	116160	88000	68200	51040	
S6-7.5	139.3	12.5									342320	264880	209880	169400	128040	99880	74360	46640