

Customize available by user request !

Model	Shuttle inner diameter(mm)	Finished coil ID Min. (mm)	enamelled copper wire diameter(mm)															
			0.07	0.08	0.09	0.10	0.11	0.12	0.13	0.14	0.16	0.18	0.20	0.24	0.30	0.35	0.40	
B2-1.0	60	1.3	wire length storage capacityy(mm )	2280	1710	1330												
B2-1.2	60	1.5		3990	2850	2090	1520											
B2-1.3	60	1.6		5890	3990	3040	2280	1900	1520									
B2-1.4	60	1.9		7220	5130	3800	2850	2470	1900	1520	1330							
B2-1.5	60	2.2			10070	7410	5700	4750	3800	2850	2470	1710						
B2-1.6	60	2.4				9120	7030	5700	4560	3800	3230	2280	1710					
B2-1.8	60	2.6					10070	7980	6650	5320	4560	3230	2470	1710				
B2-1.9	60	2.8							7790	6460	5320	3800	2850	2090	1330			
B2-2.0	60	2.9									6840	4940	3800	2850	1900	1140		
B2-2.2	60	3.3										7410	5510	4180	2660	1710	1140	
B2-2.5	60	3.8											7410	5700	3800	2280	1520	1140
Model	Shuttle inner diameter(mm)	Finished coil inner diameter Min. (mm)		enamelled copper wire diameter(mm)														
			0.15	0.19	0.23	0.27	0.31	0.35	0.40	0.45	0.50	0.55	0.60	0.70	0.80	0.90	1.00	
B4-1.6	92	2.4	wire length storage capacityy(mm )	5800	3190	2030												
B4-1.8	92	2.7		7250	4350	2610	1740											
B4-2.0	92	3.1		8700	5220	3190	2030	1450										
B4-2.25	92	3.5			7830	4930	3480	2320	1740	1160								
B4-2.5	92	4					5220	3770	2900	2030	1450	1160						
B4-2.8	92	4.5							3480	2610	1740	1450	1160	870				
B4-3.0	92	5								3770	2900	2030	1740	1160	870			
B4-3.5	92	5.7									3770	2900	2320	1740	1160	870		
B4-3.7	98	6.3									7084	5544	4312	3388	2156	1540		
B4-4.0	98	6.8										6776	5236	4312	2772	2156	1540	
B4-4.5	99	7.7										11780	8990	7130	4960	3410	2480	
B4-5.0	99	8.4											3720	3410	3410	3100	2790	2790
Model	Shuttle inner diameter(mm)	Finished coil inner diameter Min. (mm)	enamelled copper wire diameter(mm)															
			0.28	0.32	0.36	0.40	0.45	0.50	0.55	0.60	0.70	0.80	0.90	1.00	1.10	1.20	1.30	
B6-2.8	135	4.2	wire length storage capacityy(mm )	6345	4653													
B6-3.0	135	4.5		8037	5922	4230	3384											
B6-3.2	135	5.2		18612	13536	10152	7614	5499	4230									
B6-3.7	135	6				10575	8037	5922	4653	3384	2538							
B6-4.2	139	6.9					9729	7191	5499	4230	3384	2115						
B6-4.7	139	7.9							10152	8037	6345	4230	2961	2115				
B6-4.9	139	8.2								11844	9306	6345	4653	3384	2538			
B6-5.2	139	9.1									10998	7614	5499	3807	2961	2115		
B6-5.8	139	10.2										10575	7614	5922	4230	3384	2538	
B6-6.3	139	11.2											9306	6768	5076	3807	2961	2538