

Customize available by user request !

Shuttle model	Shuttle width(mm)	Shuttle outside diameter (mm)	enamelled copper wire diameter(mm)																
			3.00	2.50	2.30	2.00	1.80	1.50	1.40	1.20	1.12	1.00	0.90	0.80	0.70	0.62	0.55	0.50	
SS300-G01/7	7	250	wire length storage capacity(m)				8.64	10.08	15.12	18	23.76	28.8	35.28	46.8	68.4	72			
SS300-G01/8	8	250					12.96	18	23.04	28.8	39.6	46.8	61.2	72	93.6	122.4			
SS300-G01/9	9	250					16.56	21.6	28.8	34.56	46.8	56.88	72	86.4	108	140.4			
SS300-G02/10	10	300		9.8	14.3	17	22.4	28.75	41.3	47.6	67.3	76.3	104	116.8	148.2	197.6			
SS300-G02/12	12	300		12.5	17.9	20.6	27.8	34.14	50.3	58.4	78.1	89.8	113.2	136.5	176	233.6			
SS300-G02/15	15	300		15.27	22.4	26	35	43	62.9	85.3	97.9	108.7	141	173.4	221	283			
SS300-G03/3	3	250									8.64	10.8	14.4	19.44	26.64	34.56	40.32	56.16	68.4
SS300-G03/5	5	250									15.12	20.16	25.2	30.24	38.8	50.4	61.2	93.6	115.2
SS300-G03/6	6	250									18.72	23.76	32.4	36.72	46.8	61.2	76.32	104.4	140.4